

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an electrical hand-held tool for producing at least a percussion movement, e.g., a hammer drill or chisel hammer with, preferably, a pneumatic percussion mechanism.

2. Description of the Prior Art

Electrical hand-held tools with a pneumatic percussion mechanism are used for generating percussions of a reciprocating oscillation movement which is transmitted to a gas spring arranged between a piston, which is sealingly displaceable in a hollow cylinder relative thereto, and an axially spaced for the piston, sealingly movable percussion means. A rotational movement of an electrical drive is transformed, at least partially, by a suitable transformation gear, primarily by an eccentric oscillator or a wobbling oscillator, in a reciprocating movement of the piston. With a correct use, a counterforce, which acts in the axial direction of the tool, acts, in the path of application of a force (force path), as a reaction percussion or impact via the working tool, the percussion mechanism, the transformation gear and its support on the tool

causes application of disturbing vibration to a person who applies the force to the tool.

From the physics of constrained amplitude oscillations of a suspended pendulum, it is basically known that it is possible to effectively dampen particularly high oscillation amplitudes in case of resonance or reverse the oscillation amplitudes by widely spaced from each other, resonant and oscillation frequencies. With the resonant or natural frequency of the suspended pendulum, the oscillating mass and the spring constant which, with a simple percussion, electrical hand-held tool, are defined by the tool mass and the spring constant of the user when the user operates the tool, are dampened. Therefore, a certain oscillation amplitude of the percussion, electrical hand-held tool is determined dependent on the number of percussions that defines the oscillation frequency.

Sub a¹⁷ U.S. Patent No. 3,918,535 discloses arrangement of a preloaded compression spring in the force path between the axially displaceable percussion mechanism and the housing in order to increase the spacing between the operating points. The spring partially oscillatingly decouples the first axially displaceable subassembly, which includes the percussion mechanism,

09046931.050101
FOI0907E694860

from the second subassembly which includes the housing. Thereby, the relative movement of the first subassembly with respect too the housing, which is caused by the partial oscillating separation of the first and second subassemblies, can be dampen by using a damping element. The resulting system of two decoupled, acting in the same direction, oscillators contains a relatively small mass of the first subassembly, which includes the percussion mechanism, and it is the first subassembly that is subjected to strong oscillations as a result of the recoil of the percussion. The relatively large mass of the second subassembly, which includes the housing, is subjected, dependent on its resonant frequency, only to constrained oscillations with a small oscillation amplitude.

The damping of the recoil energy by a relative movement of the second subassembly using a damping element depends basically on the dissipated portion of the deformation energy of the damping element. The recoil energy damping increases with the increase of the deformation force amplitude and the deformation path amplitude.

U.S. Patent No. 5,927,407 discloses the use of six elastomeric components for reducing the oscillations of oscillatingly decoupled

subassemblies of a hand-held tool. The elastomeric components act in the axial direction, and their viscous elastic energy dissipation is optimized in accordance with the oscillation frequency. The foregoing solution permits to reduce the oscillation amplitude only relatively to the case when a damping element is used.

Sub a²⁷ Accordingly, an object of the present invention is to provide a percussion, electrical hand-held tool having reduced oscillations in comparison with the conventional tools.

Another object of the present invention is to provide a substantially wear-free driving chain between two, movable relatively to each other, oscillatingly decoupled, subassemblies of a percussion, electrical hand-held tool.

SUMMARY OF THE INVENTION

These and other objects of the present invention, which will become apparent hereinafter, are achieved by providing an electrical hand-held tool for producing at least a percussion movement of a working tool and including an electrical drive, a first subassembly including a percussion mechanism and a rotor of the electrical drive rotatable about a rotor axis extending parallel to an

oscillation path of the first subassembly, and a second subassembly including a housing in which the first subassembly is supported for a limited movement along a tool axis.

Thus, the first subassembly includes, in addition to the percussion mechanism, the rotor of the electrical drive which rotates about a rotor axis extending parallel to the oscillation path of the first subassembly, and the second subassembly includes the stator of the electrical drive and the housing. Advantageously, the first subassembly includes the transformation gear which transforms the rotational movement of the rotor in the reciprocating movement of the percussion mechanism.

As a result of incorporation of the rotor and the transformation gear into the first subassembly, in addition to the percussion mechanism, the oscillating mass of the first subassembly increases with respect to the mass of the second subassembly which includes the stator, the housing and the electrical drive electronics. The absolute increase of the mass of the first subassembly results in reduction of the oscillation amplitude of the first subassembly which is determined by the recoil energy.

The mass ratio of the two subassemblies is shifted toward the first subassembly so that, finally, the two subassemblies have substantially the same mass. As a result, the damping element, which is provided between the two subassemblies, can dissipate more recoil energy, which reduces the oscillation amplitude of the second subassembly that includes the housing.

Advantageously, the damping element is formed of a viscous elastic material which dissipates a large amount energy at the oscillation frequency in the range of the operational temperatures of a percussion hand-held tool.

Summary The driving chain for generating the percussions and/or rotational movement of the electrical hand-held tool has substantially wear-free coupling means which provide for the relative movement. The coupling means is formed as a torque spanner coupling, with a magnetic rotary field of the stator acting on the axially displaceable, collectorless rotor. In particular, mechanical force-transmitting and, therefore, wear-susceptible coupling for compensation of the relative movement between the two subassemblies becomes unnecessary. With the use of the collectorless rotor, the collectors, which are susceptible to wear during the axial movement, are also eliminated.

The novel features of the present invention, which are considered as characteristic for the invention, are set forth in the appended claims. The invention itself, however, both as to its construction and its of operation, together with additional advantages and objects thereof, will be best understood from the following detailed description of preferred embodiment, when read with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS:

Single Figure of the drawings shows a side, partially cross-sectional view of a percussion, electrical hand-held tool according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Sub 47 A percussion, electrical hand-held tool 1 according to the present invention, which is shown in the drawing, includes a first subassembly with a percussion mechanism 2. The first subassembly is supported for a limited displacement along the tool axis A, e.g., 10mm, by, e.g., slide or roller bearings. The percussion mechanism 2 includes a reciprocating piston 3 and a

09846931 050101
TO: "TESSO"
transformation gear 4 including an eccentric and two conical gears ingaging each other at a right angle. The tool 1 further includes a collectorless rotor 5 of an electrical drive. The rotor 5 rotates about the rotor axis B and is supported for a limited axial displacement along the axis B parallel to a first oscillation path I of displacement of the first subassembly. Still further, the tool 1 includes a second subassembly displaceable along the second oscillation path II. The second subassembly includes a housing 6, a stator 7 of the electrical drive, and an associated control electronics 8 for the electrical drive. The second subassembly is protected from oscillations, which take place along the oscillation paths I-II, with respect to the first subassembly by a preloaded spring 9, e.g., a helical compression spring, and, with respect to the oscillation along the path II, by a damping element 10 which extends parallel to the spring 9 and is made of a viscous elastic material.

Though the present invention was shown and described with references to the preferred embodiment, such is merely illustrative of the present invention and is not to be construed as a limitation thereof, and various modifications of the present invention will be apparent to those skilled in the art. It is, therefore, not intended that the present invention be limited to the disclosed embodiments

or details thereof, and the present invention includes all variations and/or alternative embodiments within the spirit and scope of the present invention as defined by the appended claims.

094691 09101
FOF050 F694860